

# ASLAN TF 105

## The minted, transparent filmic tape

This application tape allows the transfer of graphics and letterings cut out or punched out of self-adhesive films. A special stamping of the tape allows an easier and bubble-free application and cares for an optimal handling.

ASLAN TF 105 is rolled upon itself and highly transparent.

For any further information please contact our technical advisory service:  
**+49 (0)2204.708-80**

### CONSTRUCTION

face-film:	PET
thickness:	~ 110 µm
adhesive:	acrylic pressure adhesive

### CHARACTERISTICS

adhesive strength: (ASTMD-903)	after 30 minutes	~ 2.5 N/25 mm
	after 1 week	~ 3 N/25 mm
tensile strength:	DIN 53 455	longitudal: ~ 150 % lateral: ~ 150 %
temperature:	application temperature:	min. 15°C
	service temperature range:	-30 °C up to +80 °C

### PROCESSING

application:	Dry application only. Longer application processes and high temperatures increase the adhesive strength.  To transfer the with the tape sticked lettering turn it around and remove the silicon cardboard in a angle of 180°.
storage life:	Tilt the adhesive to cure. If the tape stands in its original carton it must be stored at room temperature and 40-50% humidity and protected from direct solar radiation.

state: 11|2008

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended.

The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.

**ASLAN, Schwarz GmbH & Co. KG**

POB 5165 · D-51486 Overath · Oberauel 2 · D-51491 Overath · Germany

fon +49(0)2204.708-80 · fax +49(0)2204.708-50 · e-mail info@ASLAN-schwarz.com

**www.ASLAN-schwarz.com**