

ASLAN TL 10

The concentrate for transfer-liquids

An application of self-adhesive films onto damped smooth surfaces, like glass signifies an enormous saving of time and enables an easy positioning, because the film stays flexible and repositionable. For a damp application of self-adhesive films it's advisable to use a transfer-liquid.

ASLAN provides a transfer-liquid-concentrate including an empty spray flask for the production of unwounded water for the pre-treatment of smooth surfaces. A bottle ASLAN TL10 contains 0.5 litres and is mixed in proportion of 1:10 with water. The process with transfer-liquid does not affect the final adhesive tack of the self-adhesive films.

For any further information please contact our technical advisory service:
+49 (0)2204.708-80

CHEMICAL CHARACTERISTICS

Not flammable, liquid dilution from anionic and non-ionic tensides and alcohols.
No requirement to label
An EEC safety document is available.

FIRST AID MEASURES

In case of eyecontact thoroughly rinse with cold water.

PROCESSING

Before the application the surface should thoroughly be cleaned and evenly be sprayed with the diluted ASLAN TL 10. Afterwards align the self-adhesive film with the application tape on the still wet surface, laminate thoroughly on the surface and remove the spare liquid by using a squeegee.

Carefully remove application tape in angle of 180° and remove fluid remainings with a soft and absorbent cloth.

During wet application the adhesive might be coloured white. This will - subject to weather conditions - disappear within a few days.

state: 11|2008

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended.

The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.

ASLAN, Schwarz GmbH & Co. KG

POB 5165 · D-51486 Overath · OberaueI 2 · D-51491 Overath · Germany

fon +49 (0) 2204.708-80 · **fax** +49 (0) 2204.708-50 · **e-mail** info@ASLAN-schwarz.com

www.ASLAN-schwarz.com