

ASLAN TP 110

The application paper with low adhesive tack

This application tape with reduced adhesive power has been designed for the transfer of prints or stencil-films. ASLAN TP 110 enables also the transfer of graphics and letterings.

For any further information please contact our technical advisory service:
+49 (0)2204.708-80

CONSTRUCTION

face-film:	special paper
thickness:	~ 115 µm (paper and adhesive)
adhesive:	latex adhesive

CHARACTERISTICS

adhesive strength: (ASTMD-903)	immediately	~1.3 N/25 mm
tensile strength:	DIN 53 455	~ 3 %
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C

PROCESSING

application:	ASLAN TP 110 is applied dry only. Longer application processes and high temperatures increase the adhesive strength. For the transfer turn the lettering with the TMO around and then remove the silicon carton in an angle of 180°.
storage life:	Tilt the adhesive to cure. If the tape stands in its original carton it must be stored at room temperature and 40-50% humidity and protected from direct solar radiation. This applies especially to letterings and logos being prepared with TP 110.

state: 11|2008

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended.

The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.

ASLAN, Schwarz GmbH & Co. KG

POB 5165 · D-51486 Overath · Oberaue 2 · D-51491 Overath · Germany

fon +49 (0) 2204.708-80 · **fax** +49 (0) 2204.708-50 · **e-mail** info@ASLAN-schwarz.com

www.ASLAN-schwarz.com